


## Packet Tracer – Troubleshooting Enterprise Networks 2

### Topology



## Addressing Table

Device	Interface	IPv6 Address/Prefix	Default Gateway
R1	G0/0	2001:DB8:ACAD:A::1/64	N/A
	S0/0/0	2001:DB8:ACAD:12::1/64	N/A
	S0/0/1	2001:DB8:ACAD:31::1/64	N/A
R2	G0/0	2001:DB8:CC1E:A::1/64	N/A
	G0/1	2001:DB8:ACAD:F::2/64	N/A
	S0/0/0	2001:DB8:ACAD:12::2/64	N/A
	S0/0/1	2001:DB8:ACAD:23::2/64	N/A
R3	G0/0	2001:DB8:CAFE:2::1/64	N/A
	G0/1	2001:DB8:CAFE:3::1/64	N/A
	S0/0/0	2001:DB8:ACAD:31::2/64	N/A
	S0/0/1	2001:DB8:ACAD:23::1/64	N/A
Admin_PC1	NIC	2001:DB8:CAFE:2::2/64	FE80::3
Admin_PC2	NIC	2001:DB8:CAFE:3::2/64	FE80::3
Host_A	NIC	DHCP Assigned	DHCP Assigned
Host_B	NIC	DHCP Assigned	DHCP Assigned
TFTP Server	NIC	2001:DB8:CC1E:A::2/64	FE80::2
Outside Host	NIC	2001:DB8:CC1E:F::1/64	FE80::4

## Background

This activity uses IPv6 configurations that include DHCPv6, EIGRPv6, and IPv6 default routing. Your task is to review the requirements, isolate and resolve any issues, and then document the steps you took to verify the requirements.

## Requirements

### DHCPv6

- **Host\_A** and **Host\_B** are assigned through IPv6 DHCP configured on R1.

### IPv6 Routing

- Each router is configured with IPv6 EIGRP and uses AS 100.
- **R3** is advertising a summary route to **R2** and **R1** for the two **R3** LANs.
- **R2** is configured with a fully specified default route pointing to the **ISP**.

### Connectivity

- Devices should be configured according to the Addressing Table.
- Every device should be able to ping every other device.

